

## Installer Certification

Perma-Cote is a system providing the best available exterior and interior protection against corrosion. Proper installation is essential to ensure the best possible service life for a conduit system. To ensure the best possible PVC coated conduit installation it is recommended that installers are certified.

Qualified installation provides these benefits:

Everyone benefits!

- **The End User...**  
...receives optimum installation quality and best possible service life.
- **The Professional...**  
... benefits because of obvious concern for providing only the best to the end-user.
- **The Contractor...**  
... achieves more cost-effective installation.

Perma-Cote Installer Certification is based upon training that includes classroom and hands-on instruction encompassing:

- Proper installation techniques and tools.
- Hands-on instruction for clamping, cutting, threading, bending, and assembly of PVC coated conduit.
- Interactive discussion of techniques and troubleshooting.

Only installers who are able to present the authorized, unexpired credentials of having passed our instruction and examination are officially certified to install Perma-Cote's top quality products.

Installer certification is free of charge and available at the job site, contractor's shop, factory, or wherever it is convenient to you! For more information about Installer Certification, contact Perma-Cote at 903.843.4388.

| PERMA-COTE Certified Installer   |   |
|--|---|
| On _____, 20__   |  |
| John Doe   | PC000000  |
| NAME   |   |
| successfully completed the Installer Certification Exam and is hereby designated a Certified Installer for PVC coated conduit. |   |
| SIGNED   | EXPIRATION DATE   |
| Perma-Cote: 1100 US Highway 271 South • Gilmer, TX 75644<br>Tel: 903/843-4388 • Fax: 903/843-2655 • www.permacote.com          |   |



## Spin-It



With the Perma-Cote **Spin-It**, Perma-Cote can be tightened much faster than with conventional tools. Because the **Spin-It** never touches the coating, damage to the conduit is eliminated.

| CATALOG #     | DESCRIPTION    |
|---------------|----------------|
| SPIN-IT-3/4   | 3/4" SPIN-IT   |
| SPIN-IT-1     | 1" SPIN-IT     |
| SPIN-IT-1-1/4 | 1-1/4" SPIN-IT |
| SPIN-IT-1-1/2 | 1-1/2" SPIN-IT |
| SPIN-IT-2     | 2" SPIN-IT     |

## Plasti-Socket



**Plasti-Socket** is a fiber-glass encapsulated 3/8" drive socket for use with the square fiberglass encapsulated U bolt and beam clamp nuts used in the Perma-Cote conduit support system. The **Plasti-Socket** helps avoid coating damage from metal sockets, pliers or wrenches.

| CATALOG #        | DESCRIPTION        |
|------------------|--------------------|
| PLASTISOCKET-3/8 | 3/8" Plasti-Socket |

## Z-Wrench



**Z-Wrench** features extra wide jaws which spread the clamping force, enabling the tool to grip without marring the surface of the conduit. The "V" shaped upper jaw allows **Z-Wrench** to accommodate a wide range of conduit sizes. Shallow grooves in the upper and lower jaws provide an excellent grip.

| CATALOG # | DESCRIPTION              |
|-----------|--------------------------|
| JPZ1      | 1/2" - 1-1/4" Z-Wrench   |
| JPZ2      | 1-1/2" - 2-1/2" Z-Wrench |

## JAWS 3



**JAWS 3** are a set of aluminum-nickel-bronze vise jaws designed to replace the regular jaws in a RIGID #23 or #40-A pipe vise. They completely protect the exterior coating from damage caused by the vise jaws when cutting or threading.

| CATALOG #   | DESCRIPTION                  |
|-------------|------------------------------|
| JAWS3-#23   | JAWS3 #23 PIPE VISE          |
| JAWS3-#40-A | JAWS3 #40-A TRIPOD PIPE VISE |

## Half Shell Clamps



**Half Shell Clamps** are designed to cover a large surface area when clamping conduit, especially in a chain vise. This allows for a strong grip without damaging the exterior coating.

| CATALOG #        | DESCRIPTION                     |
|------------------|---------------------------------|
| HLF-SHL-CLP2     | 2" HALF-SHELL CONDUIT CLAMP     |
| HLF-SHL-CLP2-1/2 | 2-1/2" HALF-SHELL CONDUIT CLAMP |
| HLF-SHL-CLP3     | 3" HALF-SHELL CONDUIT CLAMP     |
| HLF-SHL-CLP3-1/2 | 3-1/2" HALF-SHELL CONDUIT CLAMP |
| HLF-SHL-CLP4     | 4" HALF-SHELL CONDUIT CLAMP     |
| HLF-SHL-CLP5     | 5" HALF-SHELL CONDUIT CLAMP     |
| HLF-SHL-CLP6     | 6" HALF-SHELL CONDUIT CLAMP     |

## Hickey



The **Perma-Cote Hickey** is a special bending tool with a 40 mil PVC coating which reduces the possibility of damage during conduit bending.

| CATALOG # | DESCRIPTION                |
|-----------|----------------------------|
| HICKEY    | 1/2" & 3/4" Conduit Bender |

## Touch Up Compounds

Perma-Cote Touch Up Compounds are available to repair minor damage to the interior urethane or exterior PVC factory coatings. The exterior PVC touchup compound is gray and available in a 12 oz. aerosol can, and a pint can with brush-top applicator.

The approved thread compound touchup compound is available in a pint can with a brush-top applicator.

See the installation section of the buyers' guide for more information on using the Perma-Cote touchup compounds.

### PERMA-COTE TOUCH UP COMPOUNDS

| CATALOG #       | DESCRIPTION                                 | SIZE   |
|-----------------|---|--------|
| TC-1700         | Exterior Spray Type (Gray)                  | 12 oz. |
| TC-1600         | Exterior Non-Spray with Brush-Top (Gray)    | 1 pt.  |
| THREAD-COMPOUND | Approved Conductive Compound-Brush-Top Pint | 1 pt.  |

